

TKT

Tactive
infokiosk



Tactive TKT is a multifunctional interactive info kiosk, particularly suitable for replacing traditional static lecterns and gives increased vitality to the information since you can easily consult digital brochures, catalogs, videos and interactive multimedia content. But also suggested for queue management systems and as an entry-level terminal for self-ordering applications. Available in 22" and 27", vertical or horizontal. Its elegance can be seen in the details of the vertical column made in an extremely compact and stable metal base. The frontal door allows for immediate access to the internal devices in order to perform simple and fast maintenance operations.

ENVIRONMENT

Indoor
IP20 (Nema 1)
IP20 (Nema 1) dust proof
Temperature range from 0°C to +40°C

STRUCTURE

Structure in steel
Frontal door for easy operations
Ergonomic design for disabilities
Fully customizable

TECHNOLOGY AND USAGE

250/500 nit brightness
24/7 usage
Primary brand PRO grade LCD
PCAP touch as standard
Front panel for device integration

AVAILABLE SIZES

portrait

22" 27"

landscape

22" 27"



For more information visit www.fida.it

Copyright © 2023 Fida srl

	TKT.P22	TKT.L22	TKT.P27	TKT.L27
--	---------	---------	---------	---------

General

	Portrait	Landscape	Portrait	Landscape
Screen orientation	Portrait	Landscape	Portrait	Landscape
Screen size (inch)	21,5"		27"	
Screen active area (cm)	26,8 X 47,6		34 X 60	
Display brightness (nit)	250		255	
Screen resolution (pixel)	Full HD - 1920x1080		Full HD - 1920x1080	
Contrast ratio (typ)	3000:1 (typ)		3000:1 (typ)	
Viewing angle (H/V)	178° / 178°		178° / 178°	
Backlight Life Cycle	50.000 hours		50.000 hours	
System operation	24/7/365		24/7/365	
Screen side	Single		Single	
Touchscreen	PCAP 10P		PCAP 10P	

Environment

Environment protection	Indoor - IP20 (Nema 1)	Indoor - IP20 (Nema 1)
Sun exposure	not allowed	not allowed
Operating temperature	"0°C / +40°C "	"0°C / +40°C "
Environment humidity	10% - 80%	10% - 80%
Antivandal protection	--	--

Enclosure

Air cooling system	passive dissipation	passive dissipation
Enclosure material	galvanized steel	galvanized steel
Glass	standard	standard
Glass reflection	--	--
Standard enclosure color	White (RAL9010)	White (RAL9010)
Standard glass color	Black (RAL 9004)	Black (RAL 9004)

Power

Vac supply	230V AC +/- 10	230V AC +/- 10
Power consumption (typ)	50 W	60 W

Dimensions

Height (cm)	90	82	100	92
Width (cm) [Base]	32 [40]	53 [40]	39 [40]	62 [40]
Depth (cm)	35	35	35	35
Weight (Kg)	26	26	28	28
Notes				

